

PRODUCT

Acoustic metallic door

GENERAL DESCRIPTION

Metallic folding pivot door, with universal locking system.



Index of acoustic noise insulation according to UNE-EN ISO 140-3: 1995 Rw 43 dB.

Test nº 21.005.591, realized by LGAI de Barcelona.

Available in one and two leaves.

Its uses and applications are determined where there is a need to reduce airborne noise by 43 dB compared to the other side of the door where it is generated, thus, leisure areas, engine rooms, meeting rooms, isolation rooms, recording studios, rooms suitable for acoustic regulations,... can be one of the places where to place the acoustic door.

They are doors with four sides frame, including the bottom, to ensure optimum insulation.

They are supplied in galvanized without final finishing, in this way the customer can finish it according to his needs.

USE



Residential



Industrial



Institutional
and Special


They are used in places where noise must be reduced by 43 dB from the other side of the door where it is generated. They are suitable for installation in leisure areas, engine rooms, meeting rooms, isolation rooms, recording studios,...

FEATURE OF PRODUCT



43 dB

Acoustic isolation



Index of acoustic noise insulation according to UNE-EN ISO 140-3: 1995 Rw 43 dB.

Test nº 21.005.591, realized by LGAI de Barcelona.

Products benefits according to laboratory tests:

Applus⁺
LGAi